



Safety Data Sheet

1. Product Identifier and Company Identification

Product name	: Desert Brand Master Seal 100 VOC – Clear & Pigmented	
HBCC SDS number	: CD05001-CD5009	
Synonym	: DBMS Clear Sealer	
Product use and Restrictions	: Refer to label or call	
Manufacturer	: Corporate Headquarters	Corporate Safety & Compliance
Contact Address	Hill Brothers Chemical Company 1675 North Main Street Orange, California 92867 714-998-8800 – Office 800-821-7234 – Office	Hill Brothers Chemical Company 7121 West Bell Road, Suite 250 Glendale, Arizona 85308 623-535-9955 - Office 623-535-9944 - Fax
Emergency Telephone Number (Chemtrec)	: 800-424-9300	
Website	: http://hillbrothers.com	

2. Hazard Identification

Classification : Flammable Liquid: Category 2
Skin Corrosion/Irritation: Category 3
Serious Eye Damage/Eye Irritation: Category 2A
Specific Target Organ Toxicity (Single Exposure): Category 3

Signal Word : Danger

Pictogram(s) :



Hazard Statements : H225: Highly flammable liquid and vapor.
H316: Causes mild skin irritation.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.

Precautionary Statements

Response : P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower).
P332+P313: If skin irritation occurs: get medical advice/attention.
P304+P340+P312: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel

unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: get medical advice/attention.

P370+P378: In case of fire: Use water to extinguish.

Prevention

- : P210: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
- P233: Keep container tightly closed.
- P240: Ground and bond container and receiving equipment.
- P241: Use explosion-proof electrical, ventilating, and lighting equipment.
- P242: Use non-sparking tools.
- P243: Take action to prevent static discharges.
- P261: Avoid breathing fumes, mists, vapor, and spray.
- P264: Wash hands thoroughly after handling.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves, protective clothing, eye protection, and face protection.
- P403+P235: Store in a well-ventilated place. Keep cool.

Storage

- : P405: Store locked up.

Disposal

- : P501: Dispose of contents and container in accordance with local, regional, national, and international regulations.

3. Composition/Information on Ingredients

CAS Number	Ingredient Name	Weight %
28262-63-7	Poly (Methyl methacrylate/n-Butyl methacrylate) Acrylic Resin	<25%
66402-68-4	Ceramic Microspheres	<25%
98-56-6	p-Chlorobenzotrifluoride	<55%
13463-67-7	Titanium Dioxide	<15%
1330-20-7	Xylene	<1,5%
71808-49-6	C-11 Ketones	<2%
67-64-1	Acetone	<10%
2530-83-8	3-glycidyloxypropyltrimethoxysilane	<2%
108-65-6	Propylene Glycol Monomethyl Ether Acetate	<2%
1309-37-1	Red Oxide Pigment	<1.5%
51274-00-1	Yellow Oxide Pigment	<2.5%
1333-86-4	Carbon Black	<1%
14808-60-7	Crystalline Silica	<0.1%

4. First Aid Measures

Ingestion

- : If ingested, **DO NOT INDUCE VOMITING**. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. GET MEDICAL ATTENTION IMMEDIATELY.

Inhalation

- : Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. GET MEDICAL ATTENTION

- Skin** : IMMEDIATELY.
: Wash with soap and water. Remove contaminated clothing and shoes; do not reuse until cleaned. If persistent irritation occurs, GET MEDICAL ATTENTION IMMEDIATELY.
- Eyes** : If splashed into eyes, flush with water for 15 minutes while holding eyelids open or until irritation subsides. If irritation persists, GET MEDICAL ATTENTION IMMEDIATELY.
- Medical Conditions** : Skin contact may aggravate an existing dermatitis.
- Effects of Overexposure** : High vapor concentrations (greater than approximately 1000 ppm) are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic, and may have other central nervous system effects.
- Summary of Acute Health Hazards** : N/A
- Ingestion** : Liquid ingestion may result in vomiting or abdominal pain.
- Inhalation** : High vapor/aerosol concentrations (greater than approximately 1000 ppm) are irritating to the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Negligible hazard at ambient temperature (-18 to 38°C; 0 to 100°F) and normal ventilation.
- Skin** : Prolonged and repeated liquid contact can cause drying of the skin which may result in skin irritation and dermatitis.
- Eyes** : May cause eye irritation on contact.
- Note to Physicians** : N/A
- Summary of Chronic Health** : N/A

Signs and Symptoms of Exposure: Prolonged or repeated skin contact with this product tends to remove oils possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

5. Fire Fighting Measures

- Extinguishing** : Use water fog, foam, dry chemical or CO₂. Do not use a direct stream of water. Product will float and can be reignited on surface of water.
- Special Exposure Hazards** : Handle as a flammable material! Vapors may form an explosive mixture with air between the upper and lower explosive limits. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. When exposed to extreme temperature, closed containers may explode. Vapor could travel toward a source of ignition and flash back.

Special Protective Equipment for Firefighters

: Wear proper protective clothing including a NIOSH approved self-contained breathing apparatus.

Fire Fighting Procedures

: Evacuate hazard area of unprotected personnel. Cool fire-exposed containers with a water mist.

NFPA Rating

: Health - 2
Flammability - 3
Instability - 0



0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

Uniform Fire Code Rating

: Class IB Flammable Liquid.

6. Accidental Release Measures

Personal Precautions

: Keep people away. Minimize breathing of vapors and skin contact. Ventilate confined spaces. Open all windows and doors.

Emergency Procedures

: Shut off and eliminate all ignition sources.

Methods of Containment And Clean-Up

: Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent such as sand, earth or other suitable absorbent to spill area. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas.

7. Handling and Storage

Safe Handling

: CAUTION: Flammable! Keep away from heat, sparks and open flames. Do not weld, heat or drill on or near container; even apparently emptied containers can contain explosive vapors.

Wear personal protective equipment.
Use only in well-ventilated areas.
Keep container tightly closed.
Do not use air pressure to unload containers.
Do not smoke.
Do not swallow.
Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing.

Storage

: Keep containers tightly closed. Store product away from strong oxidizing agents and in a cool, dry place with adequate ventilation. Ground your equipment to prevent accumulation of static charge. If pouring or transferring materials, containers must be bonded and grounded.

Caution: Flammable! Keep away from heat, sparks and open flames. Keep containers tightly closed. Store away from strong oxidizing agents in a cool, dry place. If pouring or transferring materials, containers must be grounded.

Work/Hygienic Practices

: Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove any contaminated shoes and thoroughly clean and dry them before reuse. Wash skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Ventilation

: Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. Use explosion-proof equipment only.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Chemical Name: Desert Brand Master Seal 100 Clear & Pigmented				
Exposure Limits (TWAs) in Air				
CAS Number	Chemical	ACGIH TLV	OSHA PEL	STEL
28262-63-7	Poly (Methyl methacrylate/n-Butyl methacrylate) Acrylic Resin	N/A	N/A	N/A
1330-20-7	Xylene	100 ppm	100 ppm	150 ppm
71808-49-6	C-11 Ketones	N/A	N/A	N/A
67-64-1	Acetone	200 ppm	1000 ppm	500 ppm
2530-83-8	3-glycidyloxypropyl-trimethoxysilane	N/A	N/A	N/A
108-65-6	Propylene Glycol Monomethyl Ether Acetate	N/A	N/A	N/A
238-878	Crystalline Silica	N/A	N/A	N/A

Protective Equipment

: Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact. Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

Eye Protection

: Use splash goggles or face shield when eye contact may occur.

Respiratory Protection : None required if adequate ventilation. Only MSHA or NIOSH approved respirators should be used if concentration is above 1000 ppm.

9. Physical and Chemical Properties

Appearance: Cloudy; Colorless; Various Colors	Odor: Sweet ketone odor
Odor Threshold: 1 -41 ppm	pH: N/A
Melting Point/Freezing Point: N/A	Initial Boiling Point/Range: 132° F (55.5° C)
Flash Point: 1° F	Evaporation Rate (BuAc=1): N/A
Flammability: 0.9%-12.8% v/v	Lower/Upper Explosive Limit: 0.9%/12.8% v/v
Vapor Pressure (mmHg): 5.3-185	Vapor Density (Air=1): N/A
Relative Density: 10.69 – 12.5 lbs/gal	Solubility in Water (g/100g): Insoluble
Partition Coefficient: N/A	Autoignition Temperature: 980° F (527° C)
Decomposition Temperature: 572° F (300° C)	Viscosity: N/A
% Volatiles: 68.3—69.3	Specific Gravity (Water=1): 1.28-1.5
Molecular Weight: N/A	VOC: <100 g/l or 0.833 lbs./gallon

10. Stability and Reactivity

Reactivity : N/A

Chemical Stability : Stable.

Possibility of Hazardous Reactions or Polymerizations : Hazardous Polymerization will not occur.

Conditions to Avoid : Avoid heat, sparks, and open flames.

Incompatible Materials : Strong oxidizing agents, concentrated nitric and sulfuric acids, and molten sulphur. Temperatures above ambient.

Hazardous Decomposition Products : Oxides of carbon, and acrylic monomer vapors.

11. Toxicological Information

Acute and Chronic Effects : N/A

Routes of Exposure

Ingestion : Yes
Inhalation : Yes
Skin : Yes
Eyes : Yes

Symptoms related to Physical, Chemical & Toxicological Characteristics : N/A

Numerical Measures of Toxicity : N/A

Chronic Toxicity : N/A

Carcinogenicity : N/A

Product Name: Desert Brand Master Seal 100 VOC Clear & Pigmented					
ACGIH	IARC	EPA	NIOSH	NTP	OSHA
No	Yes	No	Yes	No	No

TARGET ORGANS : N/A

12. Ecological Information

Ecotoxicity : N/A

Persistence and Degradability : N/A

Bioaccumulative Potential : N/A

Product/Ingredient	Log _{Pow}	BCF	Potential
-	-	-	-

Mobility in Soil : N/A

13. Disposal Considerations

Disposal of Container : Use non-leaking containers, seal tightly and label properly. Dispose of in accordance with applicable local, county, state and federal regulations.

14. Transport Information

UN# : UN1263
Proper Shipping Name : Paint Related Material
Hazard Class/Division : 3
Packing Group : II
Marine Pollutant : No
Special Provisions : 149, B58, IB2, T4, TP1, TP8, TP28
Emergency Response Guidebook : 2012 ERG, Guide 128, pages 194-195

Placard Advisory :



15. Regulatory Information

SARA 302 Extremely Hazardous Substances (EHS) : No chemical in this product is listed as an Extremely Hazardous Substance (EHS) under Section 302 of EPCRA.

SARA 304 Extremely Hazardous Substances (EHS) Release Notification : No chemical in this product is listed as an Extremely Hazardous Substance (EHS) which, if released to the environment in quantities at or above the substance's Reportable Quantity (RQ), would require reporting to the SERC and LEPC under Section 304 of EPCRA.

SARA 311/312 Hazards :

SARA 311/312 Hazards				
Acute	Chronic	Flammability	Pressure	Reactivity
Yes	Yes	Yes	No	No

SARA 313 Reportable Chemicals : This product contains the following chemical(s) subject to annual emissions, transfers, and/or waste management reporting under the Community-Right-to-Know provisions of EPCRA Section 313, also known as the Toxic Release Inventory (TRI) Report or Form R:
Xylenes (Mixed Isomers), CAS #1330-20-7

CERCLA Hazardous Substances : This product contains the following CERCLA hazardous substance(s) subject to the National Response Center (NRC) reporting requirements if released to the environment in quantities greater than or equal to the substance's CERCLA Reportable Quantity (RQ).
Xylene (Mixed Isomers), CAS #1330-20-7 CERCLA RQ = 100 lb. (45.4 kg.)
Acetone, CAS #67-64-1 CERCLA RQ = 5,000 lb. (2, 268 kg.)

Clean Air Act (CAA) Section 112(r) Air Pollutants : No chemical in this product is listed as an air pollutant under the U.S. Clean Air Act, Section 112(r) (40 CFR 61).

California Prop 65 Chemicals : This product does not contain any chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

Hazard Label Warning : This product requires the following hazard label warning:
Flammable, Class 3

TSCA (Toxic Substances Control Act) : All chemical substances in this product are listed on the U.S. TSCA Inventory List.

ACRONYMS:

CAS # – Chemical Abstract Services Registry Number
CFR – Code of Federal Regulations
CERCLA – Comprehensive Environmental Response, Compensation, and Liability Act
EPCRA – Emergency Planning and Community Right-to-Know Act
LEPC – Local Emergency Planning Committee
SERC – State Emergency Response Commission

16. Other Information

Revision date : 05/17/2015
Supersedes : 01/18/2007
First Issue : 01/18/2007

Chemical Family/Type : Paint

Section(s) changed since last revision : MSDS to First Issue SDS Conversion

IMPORTANT! Read this SDS before use or disposal of this product. Pass along the information to employees and any other persons who could be exposed to the product to be sure that they are aware of the information before use or other exposure. This SDS has been prepared in accordance with the Globally Harmonized System of Chemical and Labeling of Chemicals (GHS) Fifth Edition and the OSHA Hazard Communication Standard [29 CFR 1910.1200]. The SDS information is based on sources believed to be reliable. Available data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control; **Hill Brothers Chemical Company** makes no warranty, either expressed or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. Additional information may be necessary or helpful for specific conditions and circumstances of use. It is the user's responsibility to determine the suitability of this product and to evaluate risks and exercise appropriate precautions for protection of employees and others prior to use.